

ATTRACTIVE

EASY TO INSTALL

NO LEAKS



VELOCITY[®]

GASKETED DUCT

KEY BENEFITS

- Clean seams that do not require sealer or tape
- Offered on single wall, dual wall and manifolded duct
- Tapered edge profile strengthens fitting while providing ease in alignment and installation
- LEED certified low emitting sealants
- Available in most common sizes - 4" ID to 24" OD available
- Galvanized steel material
- Single Wall, dual wall, and manifolded duct
- Exceeds SMACNA's leakage class 3, at +/- 10" w.g.
- Service temperatures from -65°F to 248°F
- AVRON46[®] antimicrobial coating available

Clean, easy and fast

If you want to save time and money while installing a duct system that offers cleaner joint connections without the visual distractions of tape or sealer, you need Velocity[®] self-sealing gasketed joint system.

You will be amazed at the ease of installation of the single blade technology. The perfect choice for both concealed, exposed and architecturally exposed applications.

When you combine the labor saving features of the Velocity self-sealing gasketed duct with our manifolded product, you can design a system with tremendous labor saving capabilities. This allows you to be more competitive and realize more profit on each job.

For your next duct application, remember "We make it easy" with Velocity[®] gasketed duct from FläktGroup[®] SEMCO[®].

FläktGroup[®] SEMCO[®]
573 443 1481 | sales.semco@flaktgroup.com
www.semcohvac.com



FläktGroup[®]
SEMCO[®]